



FLR.0009

## WOODKOLL

Universal adhesive in water dispersion for wooden floors

### Packaging

- Pail 10 kg
- Pail 5 kg
- Pail 20 kg

### Application

- Notched finishing trowel

Family  
**Floortech**

Product Lines  
• **Building**  
• **Opus**  
• **Sanageb**  
• **Floor**

Components  
**Single-component**

Type  
**Adhesive and putty for flooring**

Functional Categories  
• **Bonding and filling tiles, parquet, etc.**

Appearance  
**Thick liquid**

## General description

Universal adhesive in water dispersion for gluing unpainted wooden floors, laminated parquet, lamparquet on concrete substrates or other types of absorbent substrates.


## Dosage


Use from 0.8 to 1 kg/m<sup>2</sup> of WOODKOLL depending on the type of support and the type of material to be bonded.

## Fields of application


Gluing of unpainted wooden floors, laminated parquet, lamparquet on concrete substrates or other types of absorbent substrates.

## Basic features

 Shelf-life:  
*6 months*

 Temperature of use:  
*+ 15 / + 25 °C*

 Use wearing protective gloves

 Available **colours**  
*Avana*

## Technical specifications

*Dry residue: 60-70 %*

*Viscosity (20° C; Brookfield): 75000-105000 cP*

*Walkability: 3-4 day*

## Tools cleansing

- Water

## Applicable on

- Floor screed

## Substrate preparation

Always check the humidity of the substrate and the wood with specific tools. The measurement of the humidity in the substrate must be made in depth (approx. 2-3 cm) using a carbide hygrometer in order to exclude the possible presence of highly hygroscopic substances (such as pumice, vermiculite), which can give off humidity contained in them with the consequent swelling of the floor. Do not lay on screeds which are not protected from possible rising damp (always position a suitable vapour-tight sheath). The thin or powdery cementitious substrates must be consolidated with suitable products in order to facilitate a perfect adhesion of the adhesive. Do not lay in rooms that are not fitted with windows or doors. Do not lay if the walls and ceilings of the room are not perfectly dry.

IF YOU WANT TO SOLVE IT  
 **azichem**

[www.azichem.com](http://www.azichem.com)

Updated: **24/08/2020**

General sales conditions and legal notices on

[www.azichem.com/disclaimer](http://www.azichem.com/disclaimer)

## Instructions for use

Bring the product to the environment temperature before use. Spread the adhesive on the substrate with a wide-toothed spatula (n° 5), working it in order to incorporate any residual dust. The application of the adhesive must be carried out in small areas in order to avoid the formation of the surface film before laying the wood. Before gluing, always check the humidity in the screed, which must be < 2% (do not use WOODKOLL on fast drying or anhydrite screeds). Environment temperature between 15 and 25°C, relative humidity not exceeding 75%.

Always use specific personal protection systems. Always consult the technical and safety data sheet of the product.

## Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between +10°C and +30°C.



## Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: [www.azichem.com](http://www.azichem.com). The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: [www.azichem.com](http://www.azichem.com).

It is forbidden to dispose of the product and/or packaging in the environment.

Do not use WOODKOLL for laying prefinished parquet. When laying lamparquet or strips, avoid gluing on the sides. Do not use WOODKOLL on fast drying or anhydrite screeds. Bring the product to a temperature of 20°C before application.



[www.azichem.com](http://www.azichem.com)

Updated: **24/08/2020**  
General sales conditions and legal notices on [www.azichem.com/disclaimer](http://www.azichem.com/disclaimer)

WOODKOLL is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy  
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



[www.azichem.com](http://www.azichem.com)

Updated: **24/08/2020**  
General sales conditions and legal  
notices on  
[www.azichem.com/disclaimer](http://www.azichem.com/disclaimer)

Page: **3/3**