



Family
Floortech

Type
Adhesive and putty for flooring

Product Lines
• **Building**
• **Opus**
• **Sanageb**

Functional Categories
• **Bonding and filling tiles, parquet, etc.**

Components
Single-component

Appearance
Powder

FLR.0164

SANASTUCK

Adhesive putty based on hydraulic lime, to fill vanishing points in floors

Customs Code

3824 5090

Packaging

- Bag 25 kg
- Pallet: 50 x (Bag 25 kg)

Application

- Sponge float
- Sponge

General description

Adhesive compound with high breathability and moldability, based on hydraulic lime, for the filling vanishing points between tiles etc. in horizontal and vertical applications, ecological building interventions, new buildings and in the restoration of vintage buildings and monuments.

General features

Product consisting of hydraulic lime, botticino, kaolin, calcium caseinate, ammonium salts and natural fibres. It does not contain cement, solvents, resins or radioemissive aggregates.

Dosage

Use 0.5 to 2 kg of SANASTUCK per square metre of surface to be grouted.

Fields of application

Puttying filling for vanishing points between tiles, in internal floorings of buildings.

Basic features



Maximum diameter of aggregate:
0.3 mm



Mix with water:
14-16 %



Pot-life:
60 min



Shelf-life:
12 months



Temperature of use:
+8 / +30 °C



Available colours
Light hazel

Technical specifications

Complete hardening (a 20°C): 14 day

Tools cleansing

- Water

Applicable on

- Tiles
- Floor screed

Substrate preparation

The application supports should be clean, intact, free from fouling, powder, crumbling and non-adhering parts and sufficiently moist.

Instructions for use

Pour about 2/3 of the mixing water into the mixer, or into a bucket from the building site; gradually add SANASTUCK and the water still required, continue to mix until a lump-free mixture of the desired consistency is obtained. Apply fillings as usual. The mixing water indicatively necessary is equal to 14-16% by weight (3.5 -4 litres per 25 kg bag).



www.azichem.com

Updated: **24/08/2020**

General sales conditions and legal notices on

www.azichem.com/disclaimer

Storage and preservation

Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Protect from humidity.



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

It is always essential to carry out preliminary tests to check the appropriateness of the product, depending on specific requirements,.

Cure the protection and the prolonged moist hardening of fresh exposed surfaces.

SANASTUCK is produced/distributed by



www.azichem.com



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398

Updated: **24/08/2020**
General sales conditions and legal notices on www.azichem.com/disclaimer