



Family
Intotech

Type
Finishing putty and skims

Product Lines
• **Building**
• **Opus**
• **Sanageb**

Functional Categories
• **Reconstruction, repair and maintenance of wooden structures**
• **Plastering and loose-fill of cracks and cavities on plasters and facades**

Components
Single-component

Appearance
Paste

INT.0045

FIBROSTUCK

Reinforced fibre adhesive filler,
for filling fissures and cracks

Customs Code

3214 9000

Packaging

- Pail 5 kg

Application

- Finishing trowel
- Spatula

General description

Adhesive filler, white in colour, for grouting and filling cracks and fissures and small imperfections on plasters and external walls, also in combination with SANAXIL FILLER.

General features

FIBROSTUCK is specifically formulated for filling, for the regularisation and the levelling of different types of surfaces: concrete, mineral and cement plasters, wood, etc.; it is ready-to-use and must be remixed, slowly, only upon its application

The three-dimensional reinforcement of nylon fibres provides different levels of finishing and weaving; it can be recoated directly, without resorting to fixatives or insulation materials; it allows the construction of perfect bases for the subsequent application of finishing products.

Dosage


Approximately 1.75 kg of FIBROSTUCK for each cubic decimetre of volume to be grouted (approximately 1750 kg per cubic metre).


Fields of application


Reclamation of the degenerative condition (cracks and discontinuities) of external walls, prior to the finishing operations, painting, etc.

Basic features

 Density:
1.75 kg/dm³

 Shelf-life:
12 months

 Temperature of use:
+8 / +35 °C

 Available colours
White

Technical specifications

Complete hardening (a 20°C): 24 - 48 h

Dry residue: 82.3 %

Hard to touch (a 20°C): 4 h

Tools cleansing

• Water

Applicable on

- Plasters
- Concrete
- Cement-based or lime-based mortars
- Drywall
- Wood
- Fiber-cement

IF YOU WANT TO SOLVE IT


www.azichem.com

Updated: **08/03/2021**

General sales conditions and legal notices on
www.azichem.com/disclaimer

Substrate preparation

The surfaces should be clean and free of any dirt, crumbling and non-adhering parts, dust, etc., conveniently saturated with water until they reach the condition "saturated with dry surface".

The cracks to be grouted should be preliminarily opened, cleaned, brushed and dedusted; where necessary they should also be treated with the fixative PROTECH FIX AC.

Instructions for use

Work by spreading the product with a spatula or steel trowel, grouting or skimming with one or many coats, until achieving the correct filling and/or levelling.

Avoid applying in conditions of rain and high humidity, which could compromise proper drying with consequent possibility of runoff that may continue for several days.

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between +5°C and +35°C.



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.



www.azichem.com

Updated: **08/03/2021**
General sales conditions and legal notices on www.azichem.com/disclaimer

FIBROSTUCK is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **08/03/2021**
General sales conditions and legal
notices on
www.azichem.com/disclaimer