



Family
Protech

Product Lines
• Aqua
• Building
• Opus

Components
Single-component

Type
Acrylic fixatives, paints and plasters

Functional Categories
• **Reconstruction, repair and maintenance of wooden structures**
• **Protective varnishing (painting)**

Appearance
Thick liquid

PRT.0151

PROTECH WOODPAINT

Transparent water-based varnish for exteriors highly resistant to UV rays

Customs Code

3209 9000

Packaging

- Pail 25 kg

Application

- Brush
- Sprayer

General description

Transparent glossy or satin finish, designed to protect the wood as well as to enhance its natural beauty. High quality, elastic with excellent adhesion to the support and surface hardness, it is soft to the touch. Suitable for indoor or outdoor use, it offers a lot of resistance to U.V. being equipped with radical catchers and film protectors, able to prevent the deterioration of the wood. It resists well to pollutants and abrasion from atmospheric dust, ensuring total protection of the wood against mold and parasites. Be careful with particular wood essences very rich in "LIGNINA". Especially for light colors and wood whitening, a pre-treatment with a suitable product is essential, in order to avoid unsightly yellowish stains.

Dosage

Approximately 0.10 kg of PROTECH WOODPAINT for each square meter of surface to be coated.

Fields of application

Particularly suitable for the treatment of any wooden artifact, both indoors and outdoors, when you want to give them resistance to light and being equipped with excellent filling power, even in bad weather.

Basic features



Shelf-life:
12 months



Solvent-free



Temperature of use:
+5 / +35 °C



To be applied in two coats



Use wearing protective gloves



UV-resistant



Available colours
Transparent / Azichem - acrilici

Technical specifications

Deep hardening: 24 h

Hard to touch: 30 min

Time before second coat: 2-3 h

Tools cleansing

• Water

Applicable on

• Wood

Instructions for use

Apply the varnish as it is without any dilution, making sure that the wood is perfectly clean, free from oily or greasy traces. The hardening in depth is fast enough so that it is possible to carry out the entire cycle in 24 hours.

IF YOU WANT TO SOLVE IT


www.azichem.com

Updated: **18/05/2021**
General sales conditions and legal notices on
www.azichem.com/disclaimer

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance.



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

PROTECH WOODPAINT is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **18/05/2021**
General sales conditions and legal notices on www.azichem.com/disclaimer