



PRT.0151

# SANAFARBE MARMORINO FONDO

Lime putty skim preliminary to  
marbled finishes

## Customs Code

3209 9000

## Packaging

- Pail 25 kg

## Application

- Spatula

Family  
**Protech**

Product Lines

- Opus
- Sanageb

Components  
**Single-component**

Type  
**Lime putty plasters and paints**

Functional Categories

- Masonry plastering with plasters and skims
- Renewal of wet masonry with waterproofing plasters
- Protective coating (plasters)

Appearance  
**Paste**

## General description

Mineral plaster for exteriors and interiors, based on lime putty, dust and granulometrically balanced marble grain, mineral pigments and specific agents, for the uniforming preparation of rough or wrinkled screeds, for ecological building interventions, new buildings and in the restoration of vintage buildings and monuments. Specific preparation for subsequent application of SANAFARBE MARMORINO FINITURA.

## General features

The long hardening lime putty, used as a binder, confers distinct breathable, antiseptic and anti-mildew properties. The high aptitude for polishing with spatula exalts the aesthetic, repellent and anti-fouling properties. The marble grain gives a pleasant dotted polychrome appearance.

The special formula of SANAFARBE MARMORINO FINITURA, based on long hardening lime putty, marble dust, natural pigments and minerals, gives great breathability, mildewcide and antibacterial properties to the coating.

## Dosage

From 1.0 to 1.3 kg of SANAFARBE MARMORINO FONDO for each square metre of surface to be covered.

## Fields of application

Smoothing of rough media prior to the application with marbled effect of SANAFARBE MARMORINO FINITURA. Super smooth finish to apply on SANASTOF as an alternative to the plaster finish.

## Basic features



Highlighted product



Density:  
1.49 kg/dm<sup>3</sup>



Max. recommended thickness:  
1.5 mm



Shelf-life:  
12 months



Temperature of use:  
+8 / +30 °C



To be applied in three coats



Available colours  
Request available colors



www.azichem.com

Updated: 24/08/2020

General sales conditions and legal notices on

www.azichem.com/disclaimer

Page: 1/3

## Technical specifications

Complete hardening (a 20°C): 16-24 h

Hard to touch (a 20°C): 4 h

## Tools cleansing

- Water

## Applicable on

- Plasters
- Cement-based or lime-based mortars

## Substrate preparation

Application surfaces should be clean, free of soiling, crumbling and non-adhering parts, dust, etc., conveniently saturated with water until they reach the condition "saturated with dry surface".

## Instructions for use

SANAFARBE MARMORINO FONDO is ready to use, in the form of a thixotropic paste and must be applied with stainless steel trowel, and in two or three coats, depending on the desired level of coverage. The last coat, unless it is provided for additional finishes, must be smoothed carefully, with a spatula or stainless steel trowel, when the product begins to dry. SANAFARBE MARMORINO FONDO can be applied to internal and external surfaces. In the case of cement plaster or lime, like in pre-existing lime-based paints, as long as they are compact and not crumbly, apply directly. Any organic type paints (washable, solvent, etc.) must be removed. Where the subsequent application of SANAFARBE MARMORINO FINITURA is planned, do not proceed with this smoothing.

## Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance.



## Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: [www.azichem.com](http://www.azichem.com). The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: [www.azichem.com](http://www.azichem.com).

It is forbidden to dispose of the product and/or packaging in the environment.

To avoid anti-adhesive effects and possible consequent detachments, take all due care to avoid "polishing" between one coat and the next. Avoid application in the presence of rainfall and high humidity.

Colours may vary slightly depending on temperature conditions at the time of spreading and during the drying and dessication phases.



[www.azichem.com](http://www.azichem.com)

Updated: **24/08/2020**  
General sales conditions and legal notices on [www.azichem.com/disclaimer](http://www.azichem.com/disclaimer)

SANAFARBE MARMORINO FONDO is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy  
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



[www.azichem.com](http://www.azichem.com)

Updated: **24/08/2020**  
General sales conditions and legal  
notices on  
[www.azichem.com/disclaimer](http://www.azichem.com/disclaimer)